

CURB CUT/GRIND & STREET CUT REQUIREMENTS

PROJECT ADDRESS: _____

CONTRACTOR: _____ (NAME) _____ (PHONE)

IS THIS CURB CUT REPLACING AN EXISTING DRIVEWAY ENTRANCE? YES NO

WILL THIS CURB/STREET CUT IMPEDE TRAFFIC OR PARKING? YES NO

IF YES, PROVIDE ADDITIONAL INFORMATION FOR TRAFFIC CONTROL: _____

CURB TO BE CUT/GROUND FOR A DISTANCE OF _____ FEET STARTING AT A POINT _____ FEET _____ OF THE _____ LOT LINE.
(DISTANCE) (DISTANCE) (N/S/E/W) (N/S/E/W)

SELECT YOUR OPTION BELOW

- CURB CUT REQUIREMENTS:**
- CUT MUST BE 24" OUT INTO THE STREET FROM BACK OF CURB
 - IF CUT IS LESS THAN 4' TO CONTROL JOINT, CONCRETE MUST BE TAKEN OUT TO JOINT.
 - CONCRETE MUST BE LIMESTONE L65 MIX
 - POUR-BACK MUST BE DOWELED EVERY 24" WITH #4 REBAR.
 - MUST BE POURED BACK 8" THICK

- STREET CUT REQUIREMENTS:**
- CUT MUST BE A MINIMUM OF 4'x4'
 - CUTS MUST BE NO LESS THAN 4' FROM EXISTING CONTROL JOINT FOR CONCRETE MUST BE REMOVED TO EXISTING JOINT.
 - CONCRETE MUST BE LIMESTONE L65 MIX
 - POUR-BACK MUST BE DOWELED EVERY 24" WITH #4 REBAR.
 - MUST BE POURED BACK 8" THICK

- CURB GRIND REQUIREMENTS:**
- CURB CAN NOT BE GROUND LOWER THAN 1/2" ABOVE EXISTING GUTTER LINE.
 - GRIND MUST BE NO LESS THAN 12" FROM CURB CONTROL JOINT.

PLEASE SHOW LOCATION OF STREET OR CURB CUT/GRIND BELOW.

The diagram shows a property layout with a dashed line for the 'PROPERTY LINE'. Below it are lines for 'SIDEWALK' and 'CURB LINE'. A street is shown at the bottom with a 'STREET NAME' box. A north arrow is on the left with the text 'INDICATE NORTH'. Two rectangular areas are outlined with dashed lines, representing potential cut locations. One is a simple rectangle, and the other is a more complex shape with an 'X' inside, possibly representing a driveway or a specific cut type.

PROPERTY LINE
SIDEWALK
CURB LINE

STREET NAME:

STREET NAME:

08/2011

INSPECTION SHALL BE MADE & APPROVED PRIOR TO POUR-BACK

PLEASE CALL THE BUILDING DEPARTMENT AT (402) 597-2072 TO REQUEST AN INSPECTION, OR FOR APPROVAL & SPECIFICATIONS.